

# MATERIAL SAFETY DATA SHEET

FIVE STAR PRODUCTS, INC.  
750 Commerce Drive  
Fairfield, CT 06825  
203-336-7900



EMERGENCY TELEPHONE NO. 1-(800) 255-3924

Issue Date: 1/3/12 Supersedes: 11/9/10

**FOR CHEMICAL  
EMERGENCY**  
Call Chem-Tel  
1-800-255-3924  
24 hrs./7days per week  
Outside US  
1-813-248-0585

## SECTION I - Product Identification: FIVE STAR® RS ANCHOR GEL

## SECTION II - Hazardous Ingredients/Identify Information

PRODUCT CLASS: Epoxy

FORMULATION IDENTIFICATION: Adhesive

Hazardous Components: Specific Chemical Identity:

<u>COMPONENT A:</u>	<u>C.A.S. No.:</u>	<u>OSHA PEL:</u>	<u>ACGIH TLV:</u>	<u>Approx. %:</u>
Modified Bisphenol A/				
Epiclorohydrin Base Epoxy Resin	25068-38-6	NE	NA	>85%
Talc	14807-96-6	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	< 8%
Coated Precipitated Calcium Carbonate	1317-65-3	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	< 8%
Titanium Dioxide	1317-80-2	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	< 2%

### COMPONENT B:

Trade Secret Amine Blend containing one or more of the following:

	694-83-7	NE	NE	<50%
	143-23-7	NE	NE	
	140-31-8	NE	NE	
	111-41-7	NE	NE	
	CAS# NE	NE	NE	
2,4,6- Tri(dimethylaminomethyl)phenol	90-72-2	10mg/m <sup>3</sup>	5mg/m <sup>3</sup>	<5%
Calcium Carbonate	471-34-1	NE	NE	>50%
Coated Precipitated Calcium Carbonate	1317-65-3	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	<5%

None of the remaining components are considered a Hazardous Material or carcinogen (1910.1200 Hazard Communication (d) 4).

NA: Not available. NE: Not established.

TRANSPORTATION INFORMATION: DOT Classification: Amines, Liquid, Corrosive, n.o.s. (aminopropyldiethanolamine);

UN 2735, Hazard Class 8, Packing Group III

## SECTION III: - Physical/Chemical Characteristics

<u>Boiling Point</u> (°F): N/E	<u>Specific Gravity</u> (H <sub>2</sub> O = 1):	A: 1.20	B: 1.64
<u>Vapor Pressure</u> (mm Hg.): N/E	<u>Melting Point</u> (°F): N/E		
<u>Vapor Density</u> : (AIR = 1): >1	<u>Evaporation Rate</u> : (Ether = 1)	>1	
<u>Solubility in Water</u> : Insoluble	<u>Appearance and Odor</u> : A: White gel, mild odor		B: Grey gel, characteristic odor.

## SECTION IV - Fire and Explosion Hazard Data

Flash Point: >200° F. Flammable Limits: LEL: N/A. UEL: N/A. Extinguishing Media: Foam, CO<sub>2</sub>, Water Fog.

Special Fire Fighting Procedures: None. Unusual Fire and Explosion Hazards: None. Avoid breathing smoke.

## SECTION V - Reactivity Data

Stability: Unstable: ( ) Stable: ( X )

Conditions to Avoid: None. Incompatibility (Materials to Avoid): Strong oxidizers, strong bases.

Hazardous Decomposition or Byproducts: CO, CO<sub>2</sub>, NOX. Hazardous Polymerization: None

Conditions to Avoid: Fires when curing.

## SECTION VI - Health Hazard Data

Carcinogenicity: No. NTP? No. IARC? No. OSHA Regulated? No.

Effects and Hazards of Overexposure (Acute and Chronic): Eyes: May produce irritation, sensitization. Skin: May produce irritation, sensitization. Inhalation (breathing): May produce irritation, sensitization. Ingestion (swallowing): May produce irritation, sensitization.

=====

**EMERGENCY AND FIRST AID PROCEDURES:**

Remove any contaminated clothing.  
Eyes: Flush immediately with large amounts of water for at least 15 minutes; contact physician immediately. Skin: Remove epoxy from skin immediately with a dry cloth or paper towel. Wash area of contact thoroughly with soap and water. SOLVENTS SHOULD NOT BE USED because they carry the irritant into the skin. Inhalation: If respiratory irritation occurs, go to fresh air. Flood work area with fresh air and if irritation continues, seek medical attention. Ingestion: Not expected. Contact medical help immediately. Untrained first aid personnel should not attempt to administer first aid. Contaminated clothing should be washed prior to re-use.

=====

**SECTION VII - Spill or Leak Procedures**

Steps To Be Taken in Case Material is Leaked or Spilled: Bind with absorbent material. Waste Disposal Method: Small Spill: Per local, state and federal regulations.

=====

**SECTION VIII - Safe Handling and Use Information**

Respiratory Protection: Respiratory protection is required when ventilation is inadequate. NIOSH/MSHA approved respirators should be provided and worn. All workers required to use respiratory protection should be trained in their proper selection, use and care. A written respirator program is outlined in 29 CFR 1910.134, and is required by OSHA. Ventilation (Local Exhaust): Recommended. Mechanical (General): Recommended. Special: Recommended; when local and mechanical ventilation is not adequate. Other: N/E. Protective Gloves: Recommended. Eye Protection: Recommended. Other Protective Equipment: Recommended; splash bib with protective clothing. Work/Hygienic Practices: Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating or smoking.

=====

**SECTION IX- Special Precautions**

Precautions to be taken in handling: Store in a cool, dry location. Do not allow the material to freeze, as product may be damaged. Store away from sparks and open flame.  
Other precautions: None.

N/A: Not available.              N/E: Not established.